

SECU

Sicherheitsprodukte GmbH

Our premium electronic lock **SECU SELO - C V.2** has a spy-proofed display. The spy-proof cursorcontrolled data input prevents unauthorized persons from deducing the secret code from the keys pressed. Individual opening rights and manipulation protection through paired lock components and Advanced Encryption Standard (AES) are further advantages for your security.

This lock type is of fully redundant design. This means that all internal electronic components controlling the lock functions are redundant. The advantage of this is that it is always possible to operate the lock using the secondary system and open the safe undamaged by a service technician in the highly unlikely event of a technical fault of the primary system.

SECU SELO - C V.2



Graphic display

Optimum operability thanks to the tilting position: all functions and settings can be used even more easily via the high-contrast graphic display.

Touch control panel

Simply touch the On button and the modern safe electronics are activated. Plus: two-colour lighting for even more comfort!

SECU SELO - C V.2

The premium electronics for our locks combine modern design with innovative technology and a high level of operating comfort based on intuitive menu navigation. The illuminated touch control panel can be activated simply by touch.

New electronics with illuminated touch control panel and graphic display

- ECB-S certified safe lock module EN 1300 class C
- Programmable electronic combination lock
- Up to 100,000,000 Setting options
- One Admin code and up to 9 User codes can be programmed
- Opening counter
- Spy-proofed display and code entry
- Modern and precise state of technology authentication process
- **Security plus:** opening delay, locking times (5 minutes after 3 incorrect code entries, then 10 minutes each time)
- Locking history can be read out on the graphic display; number of histories: 2,000
- Input unit and lock module are paired and the data communication is secured by an Advanced Encryption Standard (AES) to ensure optimum protection in case of manipulation

